J.S.	LINE FOR TRAPEZOIDAL SHEETS	L. M.	
	Line for trapezoidal sheets H42		LINE FOR TRAPEZOIDAL SHEET
/			
8002A	1 DECOILER ASSM-15T Decoiler 15 tons with loading cradle.	O	
49102A	2 COIL-CARRYING CARRIAGE		
28502	3 STRIP GUIDING UNIT		
	Strip guiding unit at the roll former's entrance		
28201B	4 ROLL FORMING LINE TYPE PME 80 Roll forming line with shaft diameter 80 mm.		
_			
14101	5 HYDRAULIC CUTTING SHEAR Cutting shear complete with hydraulic unit and cutting die		
28001	6 SERIES OF FORMING ROLLS Series of tempered and rectified rolls.		
58301B	7 UNLOADING AND STACKING BENCH Unloading and stacking bench for trapezoidal and corrugated sheets		View of the machine
36014	8 HYDRAULIC POWER PACK		
28103	9 CONTROL DESK Control desk with electrical installation.		
28701	10 ACCIDENT PREVENTION BARRIERS	U	
	Accident prevention barriers of wire netting and w. infrared rays devices		
		•	Shearing press: entry view
	PM SE Via 300	as negrappa, 109 Nonegrappa, Ve)tralv Non Satzar 145047 090 59 04 157 455058 090 90 04 157 info 04 399 04 157 info Fax w. pm.eng.info Fax w. pm.eng.info Fax w. pm.eng.info	Line for trapezoidal sheets H42
		WW @P	DM SAS Via Monte Croppo nº400 20020

SHEET METAL WORKING MACHINES

0

0



TS





Detailed view of the shear





PIEMME

LINE FOR TRAPEZOIDAL SHEETS

Line for trapezoidal sheets H42



Universal line predisposed for the production of various trapezoidal sheets with rapid change (with cassettes) on the roll forming line. From the cotrol desk besides it is possible to change the step of the trapezoidal sheet and carry out the cut to the desired length. The drawing die and the cutting knives are interchangeables, so it is possible to make various models.







Automatic unloading bench


Extraction carriage for stacked sheets

Finished product





Control panel



Decoiler with loading cradle



Decoiler capacity:	10.000	kg		
Decoiler opening: hydraulic				
Coil max. ext. Ø:	1600	mm		
Coil int. Ø :	500	mm		
Maximum width	1290	mm		
Material: galvanized, pre-painted	0.4-0.8			
Material: Aluminium	0.4-0.8			
Minimum profile length:	1500	mm		
Maximum profile length:	12000	mm		
Productivity on Lenght 3000 mm:	20	mt/1'		
Length tolerance:	±1	mm		
Line direction: to be determined				
Line colour:	6011	RAL		
*				